

## DRILL PRESSES



**MODEL MAR-255AN**  
16mm  
Bench Drill Press

### Specifications & Features:

- Motor 450W Single phase 230V 50Hz
- 16mm drill chuck
- 254mm swing
- 60mm spindle travel
- 5 spindle speeds
- Max. distance of spindle to table 370mm
- Table 198mm<sup>2</sup>
- Base size 340 x 210mm
- Column diameter 60mm
- Gross weight 42kg

**MODEL MAR-430FN**  
25mm  
Pedestal Drill Press



### Specifications & Features:

- Motor 850W Single phase 230V 50Hz
- 16mm drill chuck
- 25mm drill chuck capacity
- No.3MT spindle
- 432mm swing
- 80mm spindle travel
- 12 spindle speeds
- Table 345mm<sup>2</sup>
- Base size 460 x 275mm

- 120 - 2580 r/min
- 345mm<sup>2</sup>
- 460 x 275mm

**MODEL MAR-380AN**  
20mm  
Bench Drill Press



### Specifications & Features:

- Motor 750W Single phase 230V 50Hz
- 16mm drill chuck
- 20mm drill capacity
- No.2MT spindle capacity
- 356mm swing
- 80mm spindle travel
- 12 spindle speeds
- Max. distance of Spindle to table 370mm
- Table 290mm<sup>2</sup>
- Base size 460 x 275mm
- Column diameter 80mm
- Gross weight 73kg

**MODEL MD200BG & MD200BGE**  
Bench Grinder



### Specifications & Features:

- |                       | MD200BG    | MD200BGE   |
|-----------------------|------------|------------|
| • Wheels              |            |            |
| Diameter              | 200mm      | 200mm      |
| Thickness             | 25mm       | 25mm       |
| Arbor Hole            | 15.9mm     | 15.9mm     |
| • No load speed       | 3000r pm   | 3000rpm    |
| • Rating              | 240V, 50Hz | 240V, 50Hz |
| • Power input         | 375W       | 550W       |
| • Eye shield included |            |            |

**MODEL LG150W**  
Wet & Dry Bench Grinder



### Specifications & Features:

- |                       | Dry wheel  | Wet wheel  |
|-----------------------|------------|------------|
| • Wheel size          | 150 x 19mm | 200 x 40mm |
| • Arbor size          | 12.7mm     | 20mm       |
| • Wheel grits         | 60         | 80         |
| • Wheel speed         | 2850rpm    | 130rpm     |
| • Electric motor      |            |            |
| Power input           | 250W       |            |
| Voltage               | 230V       |            |
| Frequency             | 50Hz       |            |
| • Eye shield included |            |            |
| • Cast iron base      |            |            |
| • With water tank     |            |            |

**MODEL MD150GBS**  
Grinder/Sander  
Combo



### Specifications & Features:

- Wheels
 

Diameter	150mm
Thickness	25mm
Arbor Hole	12.7mm
- Belt size 50mm x 686mm
- No load speed 3000rpm
- Rating 240V, 50Hz
- Power input 375W

## BENCH GRINDERS

**MODEL MD250BG**  
Bench Grinder



### Specifications & Features:

- Wheels
 

Diameter	250mm
Thickness	25mm
Arbor Hole	20mm
- No load speed 3000rpm
- Rating 240V, 50Hz
- Power input 750W
- Eye shield & dust protector switch
- Stand NOT Included

**GS-B Bench Grinder Stand**

Pedestal stand used for all Martlet Bench Grinders Sold separately.



**MODEL MD150BG**  
Bench Grinder

### Specifications & Features:

- Wheels
 

Diameter	150mm
Thickness	20mm
Arbor hole	12.7mm
- No load speed 3000rpm
- Rating 240V, 50Hz
- Power input 375W
- Eye shield included.

For further information and your nearest dealer contact:  
Johannesburg: Tel: (011) 878-2600  
Durban: (031) 717-6400  
Cape Town: (021) 532-0568

or visit our showrooms at:  
Johannesburg: 77 Smit Street, Industries West Germiston.  
Durban: 12 Hellax Road, Pinetown  
Cape Town: Cnr. Van Riebeeck Drive & Jan Smuts Avenue, Beaufort West.

A **Hudaco** Group Company **Rutherford**

The manufacturer reserves the right to change specifications without notice. Standard equipment and specifications may vary in accordance with specifications issued by various countries.

# MARTLET

## Light Industrial Machinery

## TABLE SAWS



**MODEL TSC-10L**  
Tilting Arbor  
Table Saw

### Specifications & Features:

- Motor Speed 1470W Single phase 230V (2HP)
- Ruggedly constructed saw carriage for maximum cutting stability.
- Heavy, precision machined trunnions ensure accurate saw tilting.
- The fence locks securely and precisely parallel to the saw blade.
- FB4 fence & rail assy.
- Mitre gauge .
- Supplied with router ext.wing.
- Steel saw blade guard for operator safety.
- Cast iron table is precision ground.
- Open leg steel stand is standard.
- Motor speed 2850 r/min
- Diameter of Arbor 16mm
- Diameter of saw blade 254mm
- Max. depth of cut at 90° 82mm
- Max. depth of cut at 45° 54mm
- Supplied without blade
- Table with extension wing 686 x 1003mm
- Nett mass 110 kgs

**MODEL TSC-10HB**  
Heavy Duty Tilting  
Arbor Table Saw



### Specifications & Features:

- Motor 2250W Single phase 230V (3HP)
- Arbor speed 2850 r/min
- Saw arbor diameter 16mm
- Diameter of saw blade 250mm
- Max. depth of cut 90° 77mm
- Max. depth of cut at 45° 65mm
- Supplied without blade
- Solid steel stand
- FB4 fence & rail assy.
- With solid extension wing
- Table with extension wing 686 x 1003mm
- Nett mass 168 kgs

## PLANER & THICKNESSERS



**MODEL CT-150C**  
150mm Jointer

**Specifications & Features:**

- Motor 750W Single phase 230V 50Hz
- Magnetic switch No-volt and overload protection
- Dust hood
- Table 1143mm x 185mm
- Fence 710 x 102mm
- Tilt right 45°
- Positive stops 90°, 45°
- Cutting capacity depth 12.7mm
- Cutting capacity width 155mm
- Cutting capacity depth 12.7mm
- Cutting capacity rabbeting 12.7mm
- Cuts per min 15,000
- Number of knives 3
- Cabinet stand
- Gross weight 31kg



**MODEL CT-200**  
200mm Jointer

**Specifications & Features:**

- Motor 750W Single phase 230V 50Hz
- Magnetic switch no-volt and overload protection
- Table 1676.4mm x 228.6mm
- Dust hood
- Fence 914 x 101.6mm
- Tilt right & left 45°
- Cutting capacity width 206.3mm
- Cutting capacity depth 12.7mm
- Cutting capacity rabbeting 12.7mm
- Cuts per minute 15,000
- Number of knives 3
- Cabinet stand



**MODEL ML 392**  
250mm  
Planer & Thicknesser

**Specifications & Features:**

- Motor 1100W Single phase 230V 50Hz
- Planing table size 250 x 1085mm
- Thicknessing table size 250 x 600mm
- Cutting block dia. 75mm
- Feeding block dia. 40mm
- Cutting knife (pcs) 3
- Fence tilt 0 - 45° degree
- Dust chute dia. 100mm
- Planing width (max) 250mm
- Thicknessing width (max) 250mm
- Cutting depth (max) 5mm
- Thicknessing height (max) 190mm
- Cutter block speed-50 Hz 3750 r/min
- Feed Speed-50 Hz 8 m/min



**MODEL CT-381**  
380mm  
Thicknesser

**Specifications & Features:**

- Motor 1500W Single phase 230V 50Hz
- Cutting capacity:
  - Length of unbutted stock (min) 15.2mm
  - Width of stock (max) 380mm
- Thickness of stock (max) 154.4mm
- Thickness of stock (min) 6mm
- Feed rates 4.87/6.10m/min
- Cutterhead:
  - Number of knives 3
  - Diameter 73mm
  - Speed 5,000 r/min
  - Cuts per minute 15 000
- Feed rolls:
  - Spiral in-feed
  - Table bed rolls (Two)
- Table 381mm x 508mm
- Overall Dimensions:
  - Length 508mm
  - Width 710mm
  - Height (Stand) 1100mm
  - Gross weight 220kgs
  - Packing size (LxWxH) 625mm x 760mm x 735mm

## DUST EXTRACTORS

**MODEL CT-101 FM300**  
Dust Collection

**Specifications & Features:**

- Fan diameter 305mm
- Inlet diameter 127mm
- Outlet diameter 102 x 57mm
- Air suction capacity 1800 m<sup>3</sup>/h
- Bag diameter 500mm
- Bag capacity 0.153m<sup>3</sup>
- Volume rating 67 - 87dB
- Electric motor
- Power input 1500W
- Voltage 230V



**MODEL CT-201**  
Dust Collection



**MODEL MM-2315Q**  
Horizontal &  
Vertical Sander

**Specifications & Features:**

- Motor 2250W Single Phase (3HP) 230V 50Hz
- Air suction capacity 3900 m<sup>3</sup>/h
- Inlet diameter 150 or 102mm x 3
- Fan diameter 305mm
- Bag diameter 500mm
- Bag capacity 307 Litre (30 micron)
- Sound rating 75-85 db

## SANDERS

**MODEL WD12 & WD12N**  
Disc Sander



**Specifications & Features:**

- Motor WD12 550W Single Phase
- Motor WS12N 900W Single Phase 230V 50Hz
- Motor speed 1450 r/min
- Disc diameter 305mm
- Disc speed 1580rpm
- Table size 400 x 225mm square
- Table tilting up 0 - 15°
- Table tilting down 0 - 45°
- Overall dimensions (LxWxH) 550 x 420 x 450mm

## BAND SAW

**MODEL MJ-343B**  
Band Saw



**Specifications & Features:**

- Wheels diameter 350mm
- Table pivot capacity 0-45°
- Table size 500 x 400mm
- Processing scope
  - Max. height 160mm
  - Max. width 335mm
- Length of saw blade 2480mm
- Width of saw blade supplied 10mm
- Will accept blades 6-15mm wide
- 2-Line speeds of saw blade 12m/s / 10m/s
- Electric motor
  - Power 750W
  - Voltage 230V
  - Frequency 50Hz
  - Rotational speed 1400rpm
  - Gross weight 92kg

## SCROLL SAW

**MODEL SSA16L**  
Scroll Saw



**Specifications & Features:**

- Saw blade length 133mm
- Max. cutting height 50mm
- Working depth 400mm
- Lifting movement 15mm
- Bench diagonal Adjustment left degrees 0 - 45°
- Bench size 255 x 415mm
- Dimensions (L x W x H) 630 x 320 x 380mm
- Gross weight 14.5kg
- Electrical motor
  - Power 90W
  - Voltage 240V
  - Frequency 50Hz
- Built in dust blower
- Suction connection piece 35mm
- Built-in work lamp 10W

**MODEL AS-612**  
Extra Heavy Duty  
Belt & Disc Sander



**Specifications & Features:**

- Motor 750W Single Phase 230V 50Hz
- Sanding belt 150 x 1220mm
- Disc 305mm
- Sanding speed 620 m/min
- Disc speed 2800 r/min
- Magnetic switch
- Steel pulley cover

- Mitre gauge
- Work table tilts 0 - 45°
- Quick belt change
- Semi-open floor stand
- All factory standard accessories
- Gross weight 54kg

## STEEL CUT-OFF SAW



**MODEL MOD16N & MOD16B**  
Cut-Off Saws

**Specifications & Features:**

- |                    | MOD16N                   | MOD16B                  |
|--------------------|--------------------------|-------------------------|
| • Motor            | 3000W 380V 3 phase       | 2200W 220V Single phase |
| • Disc speed       | 2780 r/min               | 2800 r/min              |
| • Disc diameter    | 405mm                    |                         |
| • Cutting capacity | 40mm dia. solid material |                         |
| • Pipe             | 100mm x 6mm              |                         |
| • Square (mm)      | 100 x 100 x 10           |                         |
| • Adjustable vice  | 45° left & right         |                         |
| • Magnetic switch  |                          |                         |

**MODEL SBD-9B**  
Belt & Disc Sander



**Specifications & Features:**

- Motor 750W Single Phase 230v 50Hz
- Sanding belt 150 x 1220mm
- Disc 230mm
- (with full safety guard)
- Sanding belt Speed 310 m/min
- Sanding disc Speed 1400 m/min
- Magnetic switch
- Steel pulley cover
- Mitre gauge
- Work table tilts 0 - 45°
- Quick belt change
- Semi-open floor stand
- All factory standard accessories



**Specifications & Features:**

- Motor 1100W Single Phase 230V 50Hz
- Belts size 150 x 2010mm
- Belt speed 780m/min
- Motor speed 2900 r/min
- Max sanding length 790mm
- Standing height 600mm
- Round end dia. 70mm
- Magnetic switch safety low range
- Dust chute 102mm
- Front table 790 x 221mm
- Side table 514 x 221mm
- Ventricle height adj. 110mm
- Table tilt 45°
- Gross weight 90kgs